

# Detailed Printer Specifications

## FieldPro Series



### Printing Specifications

Printing Method: Direct thermal  
Printing Resolution: 203 dpi (8 dots per mm)  
Printing Speed: Up to 2.8 ips

### Fonts/Characters/Bar Codes

Fonts: A wide range of font types and sizes, from ~ 6 cpi to 34 cpi depending on emulation chosen, plus scaling.

International Characters: Arab-T, Arab-S, Arab-E, Asian fonts and an expanding catalog available for download.

Bar Codes: 39, 128, Intlv 2 of 5, CODABAR, EAN08 & 13, PDF-417 and UPC, depending on emulation chosen.

Downloadable fonts, graphics, logos and additional bar codes.

### Connectivity

Standard (All Units): RS232, USB

Wireless Options: Bluetooth®, Wi-Fi (802.11b), Custom RF

Software Available: Drivers for WIN 98, 2000, XP, Windows CE/Pocket PC, Windows Mobile, and Palm OS print utilities and SDK's.

Remote Printer Setup Program provides convenient configuration via a Windows interface from any computer.

Emulations: Emulates many popular printer brands (O'Neil, Zebra CPCL and ZPL, and Printek Mt3). Can be upgraded as new emulations become available.

### Print Media

Paper Type: Direct Thermal Roll

Roll Size: Maximum roll diameter 1.7" (4.3 cm), roll widths from 3.125" to 4.125" (7.6 to 10.5 cm)

Roll Capacity: Approx. 61' (18.8 m), Approximately 120 6" long receipts

Core Size: 0.75" (1.9 cm)

### Power Management

Battery: Rechargeable 2 cell Lithium Ion, (7.4 V, 2200mAh).

Endurance: Over 3,500 printed inches per charge.

Recharging: 2 hours, via on-board charger

Optional: 100 to 240 VAC wall adapter, 12 to 24 VDC in-vehicle adapter. When plugged in, the printer can be used while recharging the battery or can be run without the battery

### Physical Specifications

L x W x H: 6.1" x 5.9" x 2.7" (15.5 x 15.0 x 6.9 cm)

Weight: 20 ounces (.57 kg) with battery

### Environmental Specifications

Operating Temp: 0° to 122°F (-18° to 50°C)

Storage Temp: -4° to 140°F (-20° to 60°C)

Humidity: 10% to 90% RH (non-condensing)

Rated IP54 per IEC 529, without optional environmental case

### Operator Controls and Indicators

3 LED indicators for general fault, wireless connection/power and battery status indication. Buttons for Power and Paper Feed. Sensors for paper out, black mark detection, and door open.

### Memory Capacity

2 MB Flash, 1MB SRAM. Standard memory supports large and graphic intensive print jobs.

### Durability and Reliability

Survives multiple 4 foot drops to concrete (each face) and conforms to IEC 68-2

MTBF: 10,000 hours in normal use

### Regulatory Approvals

FCC Class B, CE mark, RoHS, WEEE, UL listed AC adapters, E-mark on In-Vehicle adapters

### Warranty

One-year printer warranty on the entire printer—case, battery, and print head included.

### Options and Accessories

- 3-Track Simultaneous Read Magnetic Card Reader, with indicator
- Universal Port
- AC Wall Adapter, 100 to 240 VAC
- In-Vehicle Power Adapter, 12 to 24 VDC
- Shoulder Strap
- Belt Loop Attachments
- Data Cables, RS232 or USB
- Environmental Case
- Spare Batteries in Multi-Packs
- Media in Case Quantities

